NOTES:UNLESSOTHERWISE SPECIFIED
THIS IS A CAD GENERATED DRAWING,DO NOT REVISE MANUALLY

REVISION HISTORY					
ZONE	REV	DESCRIPTION	E.C.O.NO	DATE	APPROVED
	1	ENGINEERING RELEASE			







LAL-1171

0.5~20GHz 低噪声放大器 Low Noise Amplifier

—电气技术参数Electrical Specifications—

频率范围 Frequency Range:	0.5 - 20GHz
增益Gain:	60dB
增益平坦度Gain Flatness:	/
噪声系数 Noise Figure:	2.0dB
输出P_{1dB} Output P_{1dB}:	22dBm
输入驻波比Input VSWR:	1.6:1
输出驻波比Output VSWR:	1.5:1
直流偏置电压DC Supply Voltage:	+12V
直流偏置电流DC Supply Current:	560mA
工作温度Operation Temperature:	-40~+85℃
存储温度Storage Temperature:	-50~+105℃

—机械技术参数Mechanical Specification—

输入连接器Input Interface：	SMA-F
输出连接器Output Interface：	SMA-F
尺寸Size(excluding connectors)：	/
重量Weight：	/

UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE MILLIMETER
TOLERANCES ARE:
DECIMALS .X±0.1 .XX±0.03 .XXX±0.012
ANGLES ±1°
FRACTIONS ±2/5

HOLE DIAMETER	TOLERANCES
.35 TO 3.20	+.05/-.02
3.21 TO 6.35	+.10/-.03
6.36 TO 12.70	+.15/-.03
12.71 TO 19.05	+.20/-.03
19.06 TO 25.40	+.25/-.03
25.41 TO 50.80	+.30/-.03

Approvals	DATE
DRWN	
ENG	
CHK	
Q.A.	

莱尔微波 Lair Microwave
www.lairmw.com sales@lairmw.com

P/N: LAL-1171

0.5-20GHz 低噪声放大器Low Noise Amplifier
增益 Gain 60dB, 噪声系数 NF 2.0dB

SIZE	CAGE NO	DWG NO.	REV
A3			1
SCALE 3:2	UNIT mm	SHEET 1 OF 1	

www.lairmw.com