


NOTES: UNLESS OTHERWISE SPECIFIED
THIS IS A CAD GENERATED DRAWING, DO NOT REVISE MANUALLY

REVISION HISTORY					
ZONE	REV	DESCRIPTION	E.C.O.NO	DATE	APPROVED
	1	ENGINEERING RELEASE			



LAL-1184

1~23GHz 低噪声放大器 Low Noise Amplifier



—电气技术参数 Electrical Specifications—

频率范围 Frequency Range:	1 - 23GHz
增益 Gain:	29dB
增益平坦度 Gain Flatness:	/
噪声系数 Noise Figure:	5.0dB
输出 P _{1dB} Output P _{1dB} :	20dBm
输入驻波比 Input VSWR:	2.0:1
输出驻波比 Output VSWR:	1.8:1
直流偏置电压 DC Supply Voltage:	+24V
直流偏置电流 DC Supply Current:	250mA
工作温度 Operation Temperature:	-40~+85°C
存储温度 Storage Temperature:	-50~+105°C

—机械技术参数 Mechanical Specification—

输入连接器 Input Interface:	SMA-F
输出连接器 Output Interface:	SMA-F
尺寸 Size (excluding connectors):	/
重量 Weight:	/

Including Heat sink

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE MILLIMETER TOLERANCES ARE: DECIMALS ANGLES FRACTIONS .XX±0.03 ±1' ±2/5 .XXX±0.012				 www.lairm.com sales@lairm.com		P/N: LAL-1184																			
<table border="1"> <tr> <td>DRWN</td> <td>DATE</td> </tr> <tr> <td>ENG</td> <td></td> </tr> <tr> <td>CHK</td> <td></td> </tr> <tr> <td>Q.A.</td> <td></td> </tr> </table>		DRWN	DATE	ENG		CHK		Q.A.		<table border="1"> <tr> <td colspan="2">1-23GHz 低噪声放大器 Low Noise Amplifier</td> </tr> <tr> <td colspan="2">增益 Gain 29dB, 噪声系数 NF 5.0dB</td> </tr> </table>		1-23GHz 低噪声放大器 Low Noise Amplifier		增益 Gain 29dB, 噪声系数 NF 5.0dB		<table border="1"> <tr> <td>SIZE</td> <td>CAGE NO</td> <td>DWG NO.</td> <td>REV</td> </tr> <tr> <td>A3</td> <td></td> <td></td> <td>1</td> </tr> </table>		SIZE	CAGE NO	DWG NO.	REV	A3			1
DRWN	DATE																								
ENG																									
CHK																									
Q.A.																									
1-23GHz 低噪声放大器 Low Noise Amplifier																									
增益 Gain 29dB, 噪声系数 NF 5.0dB																									
SIZE	CAGE NO	DWG NO.	REV																						
A3			1																						
<table border="1"> <tr> <td>HOLE DIAMETER</td> <td>TOLERANCES</td> </tr> <tr> <td>.35 TO 3.20</td> <td>+.05/-02</td> </tr> <tr> <td>3.21 TO 6.35</td> <td>+.10/-03</td> </tr> <tr> <td>6.36 TO 12.70</td> <td>+.15/-03</td> </tr> <tr> <td>12.71 TO 19.05</td> <td>+.20/-03</td> </tr> <tr> <td>19.06 TO 25.40</td> <td>+.25/-03</td> </tr> <tr> <td>25.41 TO 50.80</td> <td>+.30/-03</td> </tr> </table>		HOLE DIAMETER	TOLERANCES	.35 TO 3.20	+.05/-02	3.21 TO 6.35	+.10/-03	6.36 TO 12.70	+.15/-03	12.71 TO 19.05	+.20/-03	19.06 TO 25.40	+.25/-03	25.41 TO 50.80	+.30/-03	<table border="1"> <tr> <td>SCALE</td> <td>UNIT</td> <td colspan="2">SHEET 1 OF 1</td> </tr> <tr> <td>3:2</td> <td>mm</td> <td colspan="2"></td> </tr> </table>		SCALE	UNIT	SHEET 1 OF 1		3:2	mm		
HOLE DIAMETER	TOLERANCES																								
.35 TO 3.20	+.05/-02																								
3.21 TO 6.35	+.10/-03																								
6.36 TO 12.70	+.15/-03																								
12.71 TO 19.05	+.20/-03																								
19.06 TO 25.40	+.25/-03																								
25.41 TO 50.80	+.30/-03																								
SCALE	UNIT	SHEET 1 OF 1																							
3:2	mm																								