

NOTES:UNLESS OTHERWISE SPECIFIED  
THIS IS A CAD GENERATED DRAWING,DO NOT REVISE MANUALLY

REVISION HISTORY					
ZONE	REV	DESCRIPTION	E.C.O.NO	DATE	APPROVED
	1	ENGINEERING RELEASE			

## LAP-1018


18 – 44 GHz 功率放大器 Power Amplifier

### —电气技术参数 Electrical Specifications—

频率范围 Frequency Range:	18 – 44 GHz
增益 Gain:	42dB
输出 P <sub>1dB</sub> Output P <sub>1dB</sub> :	29dBm
饱和输出功率 Psat:	32dBm
输入驻波比 Input VSWR:	1.8:1
输出驻波比 Output VSWR:	/
直流偏置电压 DC Power Supply:	+28V
直流偏置电流 DC Current Supply:	3500mA
工作温度 Operation Temperature:	-40 ~ +85°C
存储温度 Storage Temperature:	-50 ~ +105°C

### —机械技术参数 Mechanical Specifications—

输入连接器 Input Interface:	2.92mm-F
输出连接器 Output Interface:	2.92mm-F
尺寸 Size (excluding connectors):	/
重量 Weight:	/



UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE MILLIMETER TOLERANCES ARE: DECIMALS ANGLES FRACTIONS .XX $\pm$ 0.03 $\pm$ 1' $\pm$ 2/5 .XXX $\pm$ 0.012				莱尔微波 www.lairmw.com sales@lairmw.com		P/N: LAP-1018	
HOLE DIAMETER .35 TO 3.20 3.21 TO 6.35 6.36 TO 12.70 12.71 TO 19.05 19.06 TO 25.40 25.41 TO 50.80		TOLERANCES +.05/- .02 +.10/- .03 +.15/- .03 +.20/- .03 +.25/- .03 +.30/- .03		Approvals DATE DRWN ENG CHK Q.A.		18 - 44GHz 功率放大器 Power Amplifier 增益 Gain 42dB	
SCALE 3:2		CAGE NO		DWG NO.		REV 1	
UNIT mm		SHEET 1 OF 1					