

NOTES:UNLESS OTHERWISE SPECIFIED
THIS IS A CAD GENERATED DRAWING,DO NOT REVISE MANUALLY

REVISION HISTORY					
ZONE	REV	DESCRIPTION	E.C.O.NO	DATE	APPROVED
	1	ENGINEERING RELEASE			

LAP-1059


0.5 – 22 GHz 功率放大器 Power Amplifier



—电气技术参数 Electrical Specifications—

频率范围 Frequency Range:	0.5 – 22 GHz
增益 Gain:	12dB
输出 P _{1dB} Output P _{1dB} :	27dBm
饱和输出功率 Psat:	30dBm
输入驻波比 Input VSWR:	1.6:1
输出驻波比 Output VSWR:	1.4:1
直流偏置电压 DC Power Supply:	+11V
直流偏置电流 DC Current Supply:	280mA
工作温度 Operation Temperature:	-40 ~ +85°C
存储温度 Storage Temperature:	-50 ~ +105°C

—机械技术参数 Mechanical Specifications—

输入连接器 Input Interface:	SMA-F
输出连接器 Output Interface:	SMA-F
尺寸 Size (excluding connectors):	/
重量 Weight:	/



UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE MILLIMETER TOLERANCES ARE: DECIMALS ANGLES FRACTIONS .XX±0.03 ±1' ±2/5 .XXX±0.012			 www.lairmw.com sales@lairmw.com	P/N: LAP-1059																				
	<table border="1"> <tr> <td>DRWN</td> <td>DATE</td> </tr> <tr> <td>ENG</td> <td></td> </tr> <tr> <td>CHK</td> <td></td> </tr> <tr> <td>Q.A.</td> <td></td> </tr> </table>	DRWN		DATE	ENG		CHK		Q.A.		0.5-22GHz 功率放大器 Power Amplifier 增益 Gain 12dB		<table border="1"> <tr> <td>SIZE</td> <td>CAGE NO</td> <td>DWG NO.</td> <td>REV</td> </tr> <tr> <td>A3</td> <td></td> <td></td> <td>1</td> </tr> </table>	SIZE	CAGE NO	DWG NO.	REV	A3			1			
DRWN	DATE																							
ENG																								
CHK																								
Q.A.																								
SIZE	CAGE NO	DWG NO.	REV																					
A3			1																					
<table border="1"> <tr> <td>HOLE DIAMETER</td> <td>TOLERANCES</td> </tr> <tr> <td>.35 TO 3.20</td> <td>+.05/- .02</td> </tr> <tr> <td>3.21 TO 6.35</td> <td>+.10/- .03</td> </tr> <tr> <td>6.36 TO 12.70</td> <td>+.15/- .03</td> </tr> <tr> <td>12.71 TO 19.05</td> <td>+.20/- .03</td> </tr> <tr> <td>19.06 TO 25.40</td> <td>+.25/- .03</td> </tr> <tr> <td>25.41 TO 50.80</td> <td>+.30/- .03</td> </tr> </table>	HOLE DIAMETER	TOLERANCES	.35 TO 3.20	+.05/- .02	3.21 TO 6.35	+.10/- .03	6.36 TO 12.70	+.15/- .03	12.71 TO 19.05	+.20/- .03	19.06 TO 25.40	+.25/- .03	25.41 TO 50.80	+.30/- .03	<table border="1"> <tr> <td>SCALE</td> <td>UNIT</td> <td>SHEET</td> </tr> <tr> <td>3:2</td> <td>mm</td> <td>1 OF 1</td> </tr> </table>		SCALE	UNIT	SHEET	3:2	mm	1 OF 1		
HOLE DIAMETER	TOLERANCES																							
.35 TO 3.20	+.05/- .02																							
3.21 TO 6.35	+.10/- .03																							
6.36 TO 12.70	+.15/- .03																							
12.71 TO 19.05	+.20/- .03																							
19.06 TO 25.40	+.25/- .03																							
25.41 TO 50.80	+.30/- .03																							
SCALE	UNIT	SHEET																						
3:2	mm	1 OF 1																						