

NOTES: UNLESS OTHERWISE SPECIFIED
THIS IS A CAD GENERATED DRAWING, DO NOT REVISE MANUALLY

REVISION HISTORY					
ZONE	REV	DESCRIPTION	E.C.O.NO	DATE	APPROVED
	1	ENGINEERING RELEASE			

LAP-4003


0.4 – 6.0 GHz 功率放大器 Power Amplifier



—电气技术参数 Electrical Specifications—

频率范围 Frequency Range:	0.4 – 6.0 GHz
增益 Gain:	36dB
输出 P _{1dB} Output P _{1dB} :	28dBm
输出功率三阶截断点 OIP3:	35dBm
输入驻波比 Input VSWR:	2.0:1
输出驻波比 Output VSWR:	2.5:1
直流偏置电压 DC Power Supply:	+15V
直流偏置电流 DC Current Supply:	530mA
工作温度 Operation Temperature:	-40 ~ +75°C
存储温度 Storage Temperature:	-55 ~ +125°C

—机械技术参数 Mechanical Specifications—

输入连接器 Input Interface:	SMA-F
输出连接器 Output Interface:	SMA-F
尺寸 Size (excluding connectors):	/
重量 Weight:	/



UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE MILLIMETER TOLERANCES ARE: DECIMALS ANGLES FRACTIONS .XX±0.03 ±1' ±2/5 .XXX±0.012			 www.lairmw.com sales@lairmw.com	P/N: LAP-4003	
	Approvals	DATE		0.4 - 6.0GHz 功率放大器 Power Amplifier 增益 Gain 36dB	
HOLE DIAMETER .35 TO 3.20 3.21 TO 6.35 6.36 TO 12.70 12.71 TO 19.05 19.06 TO 25.40 25.41 TO 50.80	TOLERANCES +.05/- .02 +.10/- .03 +.15/- .03 +.20/- .03 +.25/- .03 +.30/- .03	DRWN	ENG	CHK	Q.A.
		SIZE A3	CAGE NO	DWG NO.	REV 1
		SCALE 3:2	UNIT mm	SHEET 1 OF 1	