

NOTES:UNLESS OTHERWISE SPECIFIED  
THIS IS A CAD GENERATED DRAWING,DO NOT REVISE MANUALLY

REVISION HISTORY					
ZONE	REV	DESCRIPTION	E.C.O.NO	DATE	APPROVED
	1	ENGINEERING RELEASE			

## LAP-5030


50 – 3000 MHz 功率放大器 Power Amplifier

### —电气技术参数 Electrical Specifications—



频率范围 Frequency Range:	50 – 3000 MHz
增益 Gain:	11.5dB
输出 P <sub>1dB</sub> Output P <sub>1dB</sub> :	+17.5dBm
输出功率三阶截断点 OIP3:	+32.5dBm
输入驻波比 Input VSWR:	1.2:1
输出驻波比 Output VSWR:	1.3:1
直流偏置电压 DC Supply Voltage:	+12 V
直流偏置电流 DC Supply Current:	80mA
工作温度 Operation Temperature:	-40 ~ +85°C
存储温度 Storage Temperature:	-55 ~ +100°C

### —机械技术参数 Mechanical Specifications—

输入连接器 Input Interface:	SMA-F
输出连接器 Output Interface:	SMA-F
尺寸 Size (excluding connectors):	/
重量 Weight:	/



	A	B	C	D	E	F	G	H	I	J
Inch	1.250	1.250	0.563	0.450	1.000	0.625	1.000	0.250	0.500	0.187
mm	31.75	31.75	14.29	11.43	25.40	15.88	25.40	6.35	12.70	4.76

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE MILLIMETER TOLERANCES ARE: DECIMALS ANGLES FRACTIONS .X±0.1 ±1' ±2/5 .XX±0.03 .XXX±0.012				P/N: LAP-5030			
		www.lairmw.com sales@lairmw.com					
HOLE DIAMETER .35 TO 3.20 3.21 TO 6.35 6.36 TO 12.70 12.71 TO 19.05 19.06 TO 25.40 25.41 TO 50.80	TOLERANCES +.05/-02 +.10/-03 +.15/-03 +.20/-03 +.25/-03 +.30/-03	DRWN	DATE	50 - 3000MHz 功率放大器 Power Amplifier 增益 Gain 11.5dB			
		ENG		SIZE A3	CAGE NO	DWG NO.	REV 1
		CHK		SCALE 3:2	UNIT mm	SHEET 1 OF 1	
		Q.A.					