

NOTES:UNLESSOTHERWISE SPECIFIED
THIS IS A CAD GENERATED DRAWING,DO NOT REVISE MANUALLY


| REVISION HISTORY | | | | | |
|------------------|-----|---------------------|----------|------|----------|
| ZONE | REV | DESCRIPTION | E.C.O.NO | DATE | APPROVED |
| | 1 | ENGINEERING RELEASE | | | |

LAP-5037

100 – 5000 MHz 功率放大器 Power Amplifier

—电气技术参数 Electrical Specifications—

| | |
|---|----------------|
| 频率范围 Frequency Range: | 100 – 5000 MHz |
| 增益 Gain: | 15dB |
| 输出 P _{1dB} Output P _{1dB} : | +19dBm |
| 输出功率三阶截断点 OIP3: | +35dBm |
| 输入驻波比 Input VSWR: | 1.5:1 |
| 输出驻波比 Output VSWR: | 1.5:1 |
| 直流偏置电压 DC Supply Voltage: | +12 V |
| 直流偏置电流 DC Supply Current: | 85mA |
| 工作温度 Operation Temperature: | -40 ~ +85°C |
| 存储温度 Storage Temperature: | -55 ~ +100°C |



| | A | B | C | D | E | F | G | H | I | J |
|------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| Inch | 1.250 | 1.250 | 0.563 | 0.450 | 1.000 | 0.625 | 1.000 | 0.250 | 0.500 | 0.187 |
| mm | 31.75 | 31.75 | 14.29 | 11.43 | 25.40 | 15.88 | 25.40 | 6.35 | 12.70 | 4.76 |

—机械技术参数 Mechanical Specifications—

| | |
|---------------------------------|-------|
| 输入连接器 Input Interface: | SMA-F |
| 输出连接器 Output Interface: | SMA-F |
| 尺寸 Size (excluding connectors): | / |
| 重量 Weight: | / |

| | | | | | |
|--|--|---------------------------------|------|---|---------|
| UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE MILLIMETER TOLERANCES ARE: DECIMALS ANGLES FRACTIONS .X±0.1 ±1° ±2/5 .XX±0.03 .XXX±0.012 | | www.lairmw.com sales@lairmw.com | | P/N: LAP-5037 | |
| | | Approvals | DATE | 100 - 5000MHz 功率放大器 Power Amplifier 增益 Gain 15dB | |
| HOLE DIAMETER .35 TO 3.20 3.21 TO 6.35 6.36 TO 12.70 12.71 TO 19.05 19.06 TO 25.40 25.41 TO 50.80 | TOLERANCES +.05/- .02 +.10/- .03 +.15/- .03 +.20/- .03 +.25/- .03 +.30/- .03 | DRWN | ENG | CHK | Q.A. |
| | | SIZE | A3 | CAGE NO | DWG NO. |
| | | SCALE | 3:2 | UNIT | mm |
| | | REV | 1 | SHEET 1 OF 1 | |