

NOTES:UNLESSOTHERWISE SPECIFIED
THIS IS A CAD GENERATED DRAWING,DO NOT REVISE MANUALLY

REVISION HISTORY					
ZONE	REV	DESCRIPTION	E.C.O.NO	DATE	APPROVED
	1	ENGINEERING RELEASE			

LAP-5084




2 – 6 GHz 功率放大器 Power Amplifier

—电气技术参数 Electrical Specifications—

频率范围 Frequency Range:	2 – 6 GHz
增益 Gain:	33dB
输出 P _{1dB} Output P _{1dB} :	+30dBm
输出功率三阶截断点 OIP3:	+40dBm
输入驻波比 Input VSWR:	2.0:1
输出驻波比 Output VSWR:	2.5:1
直流偏置电压 DC Supply Voltage:	+28 V
直流偏置电流 DC Supply Current:	330mA
工作温度 Operation Temperature:	-40 ~ +85°C
存储温度 Storage Temperature:	-55 ~ +125°C

—机械技术参数 Mechanical Specifications—

输入连接器 Input Interface:	SMA-F
输出连接器 Output Interface:	SMA-F
尺寸 Size (excluding connectors):	/
重量 Weight:	/



	A	B	C	D	E	F	G	H	I	J
Inch	3.750	2.000	1.750	3.400	1.000	0.400	1.813	0.375	1.000	0.238
mm	92.25	50.80	44.45	86.36	25.40	10.16	46.05	9.53	25.40	6.03

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE MILLIMETER TOLERANCES ARE: DECIMALS ANGLES FRACTIONS .XX±0.1 ±1' ±2/5 .XX±0.03 .XXX±0.012				P/N: LAP-5084	
		www.lairmw.com sales@lairmw.com			
		2 - 6GHz 功率放大器 Power Amplifier 增益 Gain 33dB			
HOLE DIAMETER .35 TO 3.20 3.21 TO 6.35 6.36 TO 12.70 12.71 TO 19.05 19.06 TO 25.40 25.41 TO 50.80		TOLERANCES +.05/- .02 +.10/- .03 +.15/- .03 +.20/- .03 +.25/- .03 +.30/- .03		DRWN	DATE
				ENG	
				CHK	
				Q.A.	
		SIZE	CAGE NO	DWG NO.	REV
		A3			1
		SCALE	UNIT	SHEET 1 OF 1	
		3:2	mm		