

NOTES:UNLESS OTHERWISE SPECIFIED
THIS IS A CAD GENERATED DRAWING,DO NOT REVISE MANUALLY


REVISION HISTORY					
ZONE	REV	DESCRIPTION	E.C.O.NO	DATE	APPROVED
	1	ENGINEERING RELEASE			

LFC-5017

10 – 2000 MHz 混频器 Frequency Mixer

—电气技术参数 Electrical Specifications—

射频范围 RF Range:	10 – 2000MHz
本振范围 LO Range:	10 – 2000MHz
中频范围 IF Range:	DC – 2000MHz
LO-RF 隔离度 LO-RF Isolation:	43dB
LO-IF 隔离度 LO-IF Isolation:	35dB
RF-IF 隔离度 RF-IF Isolation:	30dB
变频损耗 Conversion Loss:	7dB
本振功率 LO Power:	17dBm
输入功率三阶截断点 IIP3:	27dBm
工作温度 Operation Temperature:	-40 ~ +85°C
存储温度 Storage Temperature:	-55 ~ +100°C



	A	B	C	D	E	F	G	H
Inch	1.250	1.250	0.563	0.625	1.000	0.625	1.000	0.250
mm	31.75	31.75	14.29	15.88	25.40	15.88	25.40	6.35

—机械技术参数 Mechanical Specifications—

RF 连接器 RF Interface:	SMA-F
LO 连接器 LO Interface:	SMA-F
IF 连接器 IF Interface:	SMA-F
尺寸 Size(excluding connectors) :	/

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE MILLIMETER TOLERANCES ARE: DECIMALS ANGLES FRACTIONS .X±0.1 ±1' ±2/5 .XX±0.03 .XXX±0.012				P/N: LFC-5017	
		www.lairmw.com sales@lairmw.com			
DRWN	DATE	10 – 2000 MHz 混频器 Frequency Mixer 本振功率 LO Power 17 dBm			
ENG		SIZE	CAGE NO	DWG NO.	REV
CHK		A3			1
Q.A.		SCALE	UNIT	SHEET 1 OF 1	
		3:2	mm		