

NOTES:UNLESSOTHERWISE SPECIFIED  
THIS IS A CAD GENERATED DRAWING,DO NOT REVISE MANUALLY

REVISION HISTORY					
ZONE	REV	DESCRIPTION	E.C.O.NO	DATE	APPROVED
	1	ENGINEERING RELEASE			

## LMA-5029


360 – 378 MHz 有源五倍频器 Active Frequency Quintupler

### —电气技术参数 Electrical Specifications—



输入频率范围 Input Frequency Range:	360 – 378MHz
输出频率范围 Output Frequency Range:	1800 – 1890MHz
输入功率 Input Power:	-5dBm
输出功率 Input Power:	+2.5dBm
谐波抑制 FO Harmonic Suppression FO:	40dB
输入驻波比 Input VSWR:	1.4:1
输出驻波比 Output VSWR:	2.1:1
直流偏置电压 DC Power Supply:	12V
直流偏置电流 DC Current Supply:	170mA
工作温度 Operation Temperature:	-40 ~ +85°C
存储温度 Storage Temperature:	-55 ~ +105°C

### —机械技术参数 Mechanical Specifications—

输入连接器 Input Interface:	SMA-F
输出连接器 Output Interface:	SMA-F
尺寸 Size (excluding connectors):	/
重量 Weight:	/



	A	B	C	D	E	F	G	H	I	J
Inch	1.250	1.250	0.563	0.450	1.000	0.625	1.000	0.250	0.500	0.187
mm	31.75	31.75	14.29	11.43	25.40	15.88	25.40	6.35	12.70	4.76

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE MILLIMETER TOLERANCES ARE: DECIMALS ANGLES FRACTIONS .XX±0.1 ±1° ±2/5 .XX±0.03 .XXX±0.012					P/N: LMA-5029		
			www.lairmw.com sales@lairmw.com		360 – 378 MHz Active Frequency Quintupler		
HOLE DIAMETER .35 TO 3.20 3.21 TO 6.35 6.36 TO 12.70 12.71 TO 19.05 19.06 TO 25.40 25.41 TO 50.80	TOLERANCES +.05/- .02 +.10/- .03 +.15/- .03 +.20/- .03 +.25/- .03 +.30/- .03	DRWN	DATE	SIZE A3	CAGE NO	DWG NO.	REV 1
		ENG		SCALE 3:2	UNIT mm	SHEET 1 OF 1	
		CHK					
		Q.A.					