

NOTES:UNLESS OTHERWISE SPECIFIED
THIS IS A CAD GENERATED DRAWING,DO NOT REVISE MANUALLY

REVISION HISTORY					
ZONE	REV	DESCRIPTION	E.C.O.NO	DATE	APPROVED
	1	ENGINEERING RELEASE			

LPD2S-2-18


2000 – 18000 MHz 功分/合路器 Power Splitter/Combiner

—电气技术参数 Electrical Specifications—

频率范围 Frequency Range:	2000 – 18000 MHz
隔离度 Isolation:	25dB(Typ.)/18dB(Min.)
插入损耗 Insertion Loss:	≤1.0dB
相位平衡 Phase Balance:	±4°
幅度平衡 Amplitude Balance:	≤0.3dB
输入驻波比 Input VSWR:	1.18(Typ)/1.4(Max)
输出驻波比 Output VSWR:	1.14(Typ)/1.3(Max)
承受功率 Power Rating:	20W(Splitter)/1W(Combiner)
工作温度 Operation Temperature:	-45 ~ +85°C

—机械技术参数 Mechanical Specifications—

输入连接器 Input Interface:	SMA-F
输出连接器 Output Interface:	SMA-F
尺寸 Size (excluding connectors):	47*42*10mm
重量 Weight:	32g



UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE MILLIMETER TOLERANCES ARE: DECIMALS ANGLES FRACTIONS .XX±0.03 ±1° ±2/5 .XXX±0.012						P/N: LPD2S-2-18			
								Approvals	DATE
HOLE DIAMETER .35 TO 3.20 3.21 TO 6.35 6.36 TO 12.70 12.71 TO 19.05 19.06 TO 25.40 25.41 TO 50.80		TOLERANCES +.05/- .02 +.10/- .03 +.15/- .03 +.20/- .03 +.25/- .03 +.30/- .03		DRWN		2000 – 18000 MHz 功分/合路器 Power Splitter/Combiner			
				ENG		SIZE A3	CAGE NO	DWG NO.	REV 1
				CHK		SCALE 3:2	UNIT mm	SHEET 1 OF 1	
				Q.A.					