

NOTES:UNLESSOTHERWISE SPECIFIED
THIS IS A CAD GENERATED DRAWING,DO NOT REVISE MANUALLY

REVISION HISTORY					
ZONE	REV	DESCRIPTION	E.C.O.NO	DATE	APPROVED
	1	ENGINEERING RELEASE			

LPD4S-2-26.5


2000 – 26500 MHz 功分/合路器 Power Splitter/Combiner

—电气技术参数 Electrical Specifications—

频率范围 Frequency Range:	2000 – 26500 MHz
隔离度 Isolation:	18dB(Typ.)/16dB(Min.)
插入损耗 Insertion Loss:	≤2.6dB
相位平衡 Phase Balance:	±6°
幅度平衡 Amplitude Balance:	±0.5dB
输入驻波比 Input VSWR:	1.7
输出驻波比 Output VSWR:	1.5
承受功率 Power Rating:	20W(Splitter)/1W(Combiner)
工作温度 Operation Temperature:	-45 ~ +85°C

—机械技术参数 Mechanical Specifications—

输入连接器 Input Interface:	SMA-F/2.92mmF
输出连接器 Output Interface:	SMA-F/2.92mm-F
尺寸 Size (excluding connectors):	73*59*10mm
重量 Weight:	/



UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE MILLIMETER TOLERANCES ARE: DECIMALS ANGLES FRACTIONS .XX±0.03 ±1' ±2/5 .XXX±0.012					P/N: LPD4S-2-26.5																								
	Approvals		DATE		www.lairmw.com sales@lairmw.com																								
<table border="1"> <tr> <td>HOLE DIAMETER</td> <td>TOLERANCES</td> </tr> <tr> <td>.35 TO 3.20</td> <td>+.05/- .02</td> </tr> <tr> <td>3.21 TO 6.35</td> <td>+.10/- .03</td> </tr> <tr> <td>6.36 TO 12.70</td> <td>+.15/- .03</td> </tr> <tr> <td>12.71 TO 19.05</td> <td>+.20/- .03</td> </tr> <tr> <td>19.06 TO 25.40</td> <td>+.25/- .03</td> </tr> <tr> <td>25.41 TO 50.80</td> <td>+.30/- .03</td> </tr> </table>		HOLE DIAMETER	TOLERANCES	.35 TO 3.20	+.05/- .02	3.21 TO 6.35	+.10/- .03	6.36 TO 12.70	+.15/- .03	12.71 TO 19.05	+.20/- .03	19.06 TO 25.40	+.25/- .03	25.41 TO 50.80	+.30/- .03	<table border="1"> <tr> <td>DRWN</td> <td></td> </tr> <tr> <td>ENG</td> <td></td> </tr> <tr> <td>CHK</td> <td></td> </tr> <tr> <td>Q.A.</td> <td></td> </tr> </table>		DRWN		ENG		CHK		Q.A.		2000 – 26500 MHz 功分/合路器 Power Splitter/Combiner			
		HOLE DIAMETER	TOLERANCES																										
.35 TO 3.20	+.05/- .02																												
3.21 TO 6.35	+.10/- .03																												
6.36 TO 12.70	+.15/- .03																												
12.71 TO 19.05	+.20/- .03																												
19.06 TO 25.40	+.25/- .03																												
25.41 TO 50.80	+.30/- .03																												
DRWN																													
ENG																													
CHK																													
Q.A.																													
		SIZE	CAGE NO	DWG NO.	REV																								
		A3			1																								
		SCALE	UNIT	SHEET 1 OF 1																									
		3:2	mm																										