

**SPDT RF Coaxial Switch 单刀双掷射频同轴开关**  
 DC to 26.5 GHz, SMA, Failsafe, 12V, Solder-Pins

型号 LR1-S26F12 是一款频率覆盖 DC-26.5GHz, SMA 型连接器, 激励电压 12Vdc, 带焊针, 立式安装单刀双掷射频同轴开关。


**RF 特性 RF Characteristics**

射频通道数量 Channel	2
频率范围 Frequency Range	DC-26.5GHz
特性阻抗 Impedance	50Ω

频率 Frequency (GHz)	DC-6	6-12	12-18	18-26.5
驻波比 VSWR (Max.)	1.20	1.25	1.40	1.60
插入损耗 Insertion Loss (dB Max.)	0.20	0.25	0.40	0.60
隔离度 Isolation (dB Min.)	70	70	60	55

**电气特性 Electrical Characteristics**

激励器 Actuator	Failsafe
激励电压 Actuator Voltage	12V
额定电流 Nominal Current (25°C±10%)	260mA
控制端接口 Actuator Terminals	Solder Pins

**机械特性 Mechanical Characteristics**

射频接口 RF Connectors	SMA-Female
寿命 Life	3,000,000 cycles
切换时间 Switching Time	≤15ms
结构 Construction	防溅型 Splashproof
重量 Weight	40g

**SPDT RF Coaxial Switch 单刀双掷射频同轴开关**  
 DC to 26.5 GHz, SMA, Failsafe, 12V, Solder-Pins

**环境特性 Environmental Characteristics**

工作温度 Operating Temperature	-25~+65°C
贮存温度 Storage Temperature	-55~+85°C

**产品外形 Outline Drawing**

控制管脚定义 PIN Definition

PIN No.	Definition	RF Continuity
"1"	+12V	RF 0↔2
"3"	GND	-

初始状态下, RF0↔1 常闭

