

NOTES:UNLESSOTHERWISE SPECIFIED  
THIS IS A CAD GENERATED DRAWING,DO NOT REVISE MANUALLY

REVISION HISTORY					
ZONE	REV	DESCRIPTION	E.C.O.NO	DATE	APPROVED
	1	ENGINEERING RELEASE			

## LSN-0007


1850 – 1990 MHz 功分/合路器 Power Splitter/Combiner

### —电气技术参数 Electrical Specifications—

频率范围 Frequency Range:	1850 – 1990 MHz
隔离度 Isolation:	21dB
插入损耗 Insertion Loss Above 3dB:	0.5dB
相位不平衡 Phase Unbalance:	1°
幅度不平衡 Amplitude Unbalance:	0.05dB
输入驻波比 Input VSWR:	1.2:1
输出驻波比 Output VSWR:	1.2:1
最大输入功率 Maximum Input Power:	+30dBm
工作温度 Operation Temperature:	-40 ~ +85°C
存储温度 Storage Temperature:	-65 ~ +150°C

### —机械技术参数 Mechanical Specifications—

输入连接器 Input Interface:	SMA-F
输出连接器 Output Interface:	SMA-F
尺寸 Size (excluding connectors):	/
重量 Weight:	/



	A	B	C	D	E	F	G	H
Inch	1.250	1.250	0.563	0.625	1.000	0.625	1.000	0.250
mm	31.75	31.75	14.29	15.88	25.40	15.88	25.40	6.35

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE MILLIMETER TOLERANCES ARE: DECIMALS ANGLES FRACTIONS .XX±0.1 ±1' ±2/5 .XXX±0.012				P/N: LSN-0007	
	Approvals	DATE		www.lairmw.com sales@lairmw.com	
HOLE DIAMETER .35 TO 3.20 3.21 TO 6.35 6.36 TO 12.70 12.71 TO 19.05 19.06 TO 25.40 25.41 TO 50.80	TOLERANCES +.05/- .02 +.10/- .03 +.15/- .03 +.20/- .03 +.25/- .03 +.30/- .03	DRWN	1850 – 1990 MHz Power Splitter/Combiner		
		ENG	SIZE	CAGE NO	DWG NO.
		CHK	A3		REV
		Q.A.	SCALE	UNIT	SHEET 1 OF 1
			3:2	mm	1