



NOTES:UNLESS OTHERWISE SPECIFIED
THIS IS A CAD GENERATED DRAWING,DO NOT REVISE MANUALLY

REVISION HISTORY					
ZONE	REV	DESCRIPTION	E.C.O.NO	DATE	APPROVED
	1	ENGINEERING RELEASE			



LVO-5033

2560 - 2875MHz 压控振荡器 Voltage Controlled Oscillator

—电气技术参数Electrical Specifications—

频率范围Frequency Range:	2560-2875MHz
调谐电压Tuning Voltage:	0.5-8.0Vdc
调谐灵敏度Tuning Sensitivity:	72MHz/V
输出功率Output Power:	+1dBm
相位噪声Phase Noise:	-93dBc/Hz@10KHz
二次谐波抑制2 nd Harmonic Suppression:	-18dBc
直流偏置电压DC Supply Voltage:	+12V
直流偏置电流DC Supply Current:	18mA
工作温度Operation Temperature:	-40~+85℃
存储温度Storage Temperature:	-55~+100℃

—机械技术参数Mechanical Specification—

输入连接器Input Interface:	SMA-F
输出连接器Output Interface:	SMA-F
尺寸Size(excluding connectors):	/
重量Weight:	/

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE MILLIMETER TOLERANCES ARE: DECIMALS ANGLES FRACTIONS .XX±0.03 ±1' ±2/5 .XXX±0.012			莱尔微波 www.lairmw.com sales@lairmw.com	P/N: LVO-5033	
	Approvals	DATE		2560-2875MHz 压控振荡器Voltage Controlled Oscillator	
HOLE DIAMETER .35 TO 3.20 3.21 TO 6.35 6.36 TO 12.70 12.71 TO 19.05 19.06 TO 25.40 25.41 TO 50.80	TOLERANCES +.05/- .02 +.10/- .03 +.15/- .03 +.20/- .03 +.25/- .03 +.30/- .03	DRWN	ENG	CHK	Q.A.
SCALE 3:2			UNIT mm	DWG NO.	REV 1
SHEET 1 OF 1					