

1	2	3	4	5	6	7	8																														
				标记 SIGN	版本 REV.	描述 DESCRIPTION	变更人 ORIGINATOR	日期 DATE	更改单号 REVISE NO.																												
				/	/	新版发行 NEW EDITION	/	/	/																												
<p>执行标准 Standard according to:GJB360B,MIL-STD-202</p> <p>电气性能 Electrical Data:</p> <ol style="list-style-type: none"> 特性阻抗 Impedance:50 Ω; 频率范围 Frequency range:DC-11GHz; 电压驻波比 VSWR:见附表 See table; 平均功率 Mean power:10W; <p>机械与环境性能 Mechanical Data And Environmental Data:</p> <ol style="list-style-type: none"> 耐久性 Durability(matings):500 times; 温度范围 Temperature range:-55 to +125℃; <p>材料及表面处理 Material Data:</p> <ol style="list-style-type: none"> 外导体 Outer Contact:不锈钢钝化 Stainless steel passivated; 内导体 Centre Contact:锡青铜镀金 Tin bronze gold-plated; 绝缘体 Insulator:PTFE; 螺套 Nut:不锈钢钝化 Stainless steel passivated; 密封垫 Gaskets:硅橡胶 Silicone rubber; 壳体Body: 铝合金阳极氧化黑色 6061-T6 black anodizing; 																																					
							<table border="1"> <tr> <td>N-JR-10W11-02</td> <td>≤1.20 (DC-11GHz)</td> </tr> <tr> <td>N-JR-10W11-01</td> <td>≤1.10 (DC-11GHz)</td> </tr> <tr> <td>P/N</td> <td>VSWR</td> </tr> </table>		N-JR-10W11-02	≤1.20 (DC-11GHz)	N-JR-10W11-01	≤1.10 (DC-11GHz)	P/N	VSWR																							
N-JR-10W11-02	≤1.20 (DC-11GHz)																																				
N-JR-10W11-01	≤1.10 (DC-11GHz)																																				
P/N	VSWR																																				
<table border="1"> <tr> <td colspan="2">未注形位公差 GENERAL TOLERANCE OF FORM AND LOCATION</td> <td colspan="2">GB/T 1184-H</td> </tr> <tr> <td colspan="2">未注尺寸公差 GENERAL DIMENSIONAL TOLERANCE</td> <td>设计 DESIGN</td> <td>Caogang 20210616</td> </tr> <tr> <td colspan="2"></td> <td>校对 CHECK</td> <td>Xuyan 20210616</td> </tr> <tr> <td colspan="2"></td> <td>审核 AUDIT</td> <td>Qzheng 20210616</td> </tr> <tr> <td colspan="2"></td> <td>工艺 TECHNICS</td> <td>LiLi 20210616</td> </tr> <tr> <td colspan="2"></td> <td>标审 STANDARDIZE</td> <td>WHlei 20210616</td> </tr> <tr> <td colspan="2"></td> <td>批准 APPROVE</td> <td>TFsheng 20210616</td> </tr> </table>				未注形位公差 GENERAL TOLERANCE OF FORM AND LOCATION		GB/T 1184-H		未注尺寸公差 GENERAL DIMENSIONAL TOLERANCE		设计 DESIGN	Caogang 20210616			校对 CHECK	Xuyan 20210616			审核 AUDIT	Qzheng 20210616			工艺 TECHNICS	LiLi 20210616			标审 STANDARDIZE	WHlei 20210616			批准 APPROVE	TFsheng 20210616						
未注形位公差 GENERAL TOLERANCE OF FORM AND LOCATION		GB/T 1184-H																																			
未注尺寸公差 GENERAL DIMENSIONAL TOLERANCE		设计 DESIGN	Caogang 20210616																																		
		校对 CHECK	Xuyan 20210616																																		
		审核 AUDIT	Qzheng 20210616																																		
		工艺 TECHNICS	LiLi 20210616																																		
		标审 STANDARDIZE	WHlei 20210616																																		
		批准 APPROVE	TFsheng 20210616																																		
		X. ±0.1 X° . ±1°		描述 DESCRIPTION		N公头负载 N Male Load																															
		.X±0.05 .X° ±0.5°		名称 NAME		射频同轴负载 RF Coaxial Load		图号 DWG No.																													
		.XX±0.05 .XX° ±0.2°		视图 VIEW		产品型号 P/N		N-JR-10W11-XX																													
		.XXX±0.02 .XXX° ±0.1°		比例 SCALE		4:1		表面积SURFACE AREA (mm ²)																													
关键尺寸 CRITICAL DIMENSION *				单位 UNIT		图幅 SIZE		重量 WEIGHT (g)																													
1		2		mm		A4		-																													
								版本 REV.																													
								V1.0																													
								页码 SHEET OF																													
								1/1																													