

1	2		3		4		5		6		7		8																																																																																								
					标记 SIGN	版本 REV.	描述 DESCRIPTION			变更人 ORIGINATOR	日期 DATE	更改单号REVISE NO.																																																																																									
					/	/	新版发行 NEW EDITION			/	/	/																																																																																									
<p>执行标准 Standard according to:GJB360B,MIL-STD-202</p> <p>电气性能 Electrical Data:</p> <ol style="list-style-type: none"> <li>特性阻抗 Impedance:50 Ω;</li> <li>频率范围 Frequency range:DC-26.5GHz;</li> <li>电压驻波比 VSWR:见附表 See table;</li> <li>平均功率 Mean power:2W;</li> </ol> <p>机械与环境性能 Mechanical Data And Environmental Data:</p> <ol style="list-style-type: none"> <li>耐久性 Durability(matings):500 times;</li> <li>温度范围 Temperature range:-55 to +125℃;</li> </ol> <p>材料及表面处理 Material Data:</p> <ol style="list-style-type: none"> <li>外导体 Outer Contact:不锈钢钝化 Stainless steel passivated;</li> <li>内导体 Centre Contact:锡青铜镀金 Tin bronze gold-plated;</li> <li>绝缘体 Insulator:PTFE;</li> <li>螺套 Nut:不锈钢钝化 Stainless steel passivated;</li> <li>密封垫 Gaskets:硅橡胶 Silicone rubber;</li> <li>壳体Body: 黄铜镀镍 Brass Nickel-plated;</li> </ol>																																																																																																					
<table border="1" style="float: right;"> <tr> <td>SSMA-JR-2W26.5A-02</td> <td>≤1.25 (DC-26.5GHz)</td> </tr> <tr> <td>SSMA-JR-2W26.5A-01</td> <td>≤1.15 (DC-26.5GHz)</td> </tr> <tr> <td>P/N</td> <td>VSWR</td> </tr> </table>															SSMA-JR-2W26.5A-02	≤1.25 (DC-26.5GHz)	SSMA-JR-2W26.5A-01	≤1.15 (DC-26.5GHz)	P/N	VSWR																																																																																	
SSMA-JR-2W26.5A-02	≤1.25 (DC-26.5GHz)																																																																																																				
SSMA-JR-2W26.5A-01	≤1.15 (DC-26.5GHz)																																																																																																				
P/N	VSWR																																																																																																				
<table border="1" style="width: 100%;"> <tr> <td colspan="4">未注形位公差 GENERAL TOLERANCE OF FORM AND LOCATION</td> <td colspan="4">GB/T 1184-H</td> <td colspan="4" rowspan="2" style="text-align: center;"> </td> </tr> <tr> <td colspan="4">未注尺寸公差 GENERAL DIMENSIONAL TOLERANCE</td> <td>设计 DESIGN</td> <td colspan="3">Caogang 20210616</td> <td colspan="2">描述 DESCRIPTION</td> <td colspan="4">SSMA公头负载 SSMA Male Load</td> </tr> <tr> <td>X. ±0.1</td> <td colspan="3">X° . ±1°</td> <td>审核 AUDIT</td> <td colspan="3">Qzheng 20210616</td> <td>名称 NAME</td> <td colspan="2">射频同轴负载 RF Coaxial Load</td> <td>图号DWG No.</td> <td colspan="3">-</td> </tr> <tr> <td>.X ±0.05</td> <td colspan="3">.X° ±0.5°</td> <td>工艺 TECHNICS</td> <td colspan="3">LiLi 20210616</td> <td>视图 VIEW</td> <td></td> <td>产品型号 P/N</td> <td colspan="4">SSMA-JR-2W26.5A-XX</td> </tr> <tr> <td>.XX ±0.05</td> <td colspan="3">.XX° ±0.2°</td> <td>标审 STANDARDIZE</td> <td colspan="3">WHlei 20210616</td> <td>比例 SCALE</td> <td>5:1</td> <td>表面积SURFACE AREA (mm<sup>2</sup>)</td> <td>-</td> <td>版本 REV.</td> <td colspan="2">V1.0</td> </tr> <tr> <td>.XXX ±0.02</td> <td colspan="3">.XXX° ±0.1°</td> <td>批准 APPROVE</td> <td colspan="3">TFsheng 20210616</td> <td>单位 UNIT</td> <td>mm</td> <td>图幅 SIZE</td> <td>A4</td> <td>重量 WEIGHT (g)</td> <td>-</td> <td>页码 SHEET OF</td> <td>1/1</td> </tr> </table>															未注形位公差 GENERAL TOLERANCE OF FORM AND LOCATION				GB/T 1184-H								未注尺寸公差 GENERAL DIMENSIONAL TOLERANCE				设计 DESIGN	Caogang 20210616			描述 DESCRIPTION		SSMA公头负载 SSMA Male Load				X. ±0.1	X° . ±1°			审核 AUDIT	Qzheng 20210616			名称 NAME	射频同轴负载 RF Coaxial Load		图号DWG No.	-			.X ±0.05	.X° ±0.5°			工艺 TECHNICS	LiLi 20210616			视图 VIEW		产品型号 P/N	SSMA-JR-2W26.5A-XX				.XX ±0.05	.XX° ±0.2°			标审 STANDARDIZE	WHlei 20210616			比例 SCALE	5:1	表面积SURFACE AREA (mm <sup>2</sup> )	-	版本 REV.	V1.0		.XXX ±0.02	.XXX° ±0.1°			批准 APPROVE	TFsheng 20210616			单位 UNIT	mm	图幅 SIZE	A4	重量 WEIGHT (g)	-	页码 SHEET OF	1/1
未注形位公差 GENERAL TOLERANCE OF FORM AND LOCATION				GB/T 1184-H																																																																																																	
未注尺寸公差 GENERAL DIMENSIONAL TOLERANCE				设计 DESIGN	Caogang 20210616							描述 DESCRIPTION		SSMA公头负载 SSMA Male Load																																																																																							
X. ±0.1	X° . ±1°			审核 AUDIT	Qzheng 20210616			名称 NAME	射频同轴负载 RF Coaxial Load		图号DWG No.	-																																																																																									
.X ±0.05	.X° ±0.5°			工艺 TECHNICS	LiLi 20210616			视图 VIEW		产品型号 P/N	SSMA-JR-2W26.5A-XX																																																																																										
.XX ±0.05	.XX° ±0.2°			标审 STANDARDIZE	WHlei 20210616			比例 SCALE	5:1	表面积SURFACE AREA (mm <sup>2</sup> )	-	版本 REV.	V1.0																																																																																								
.XXX ±0.02	.XXX° ±0.1°			批准 APPROVE	TFsheng 20210616			单位 UNIT	mm	图幅 SIZE	A4	重量 WEIGHT (g)	-	页码 SHEET OF	1/1																																																																																						
<table border="1" style="width: 100%;"> <tr> <td>关键尺寸 CRITICAL DIMENSION *</td> <td colspan="14"></td> </tr> <tr> <td>1</td> <td colspan="2">2</td> <td colspan="2">3</td> <td colspan="2">4</td> <td colspan="2">5</td> <td colspan="2">6</td> <td colspan="2">7</td> <td colspan="3">8</td> </tr> </table>															关键尺寸 CRITICAL DIMENSION *															1	2		3		4		5		6		7		8																																																										
关键尺寸 CRITICAL DIMENSION *																																																																																																					
1	2		3		4		5		6		7		8																																																																																								