

1	2		3		4		5		6		7		8																																																																											
					标记 SIGN	版本 REV.	描述 DESCRIPTION			变更人 ORIGINATOR	日期 DATE	更改单号 REVISE NO.																																																																												
					/	/	新版发行 NEW EDITION			/	/	/																																																																												
<p><b>执行标准 Standard according to:</b> GJB360B, MIL-STD-202</p> <p><b>电气性能 Electrical Data:</b></p> <ol style="list-style-type: none"> <li>特性阻抗 Impedance: 50 Ω;</li> <li>频率范围 Frequency range: DC-40GHz;</li> <li>电压驻波比 VSWR: 见附表 See table;</li> <li>平均功率 Mean power: 2W;</li> </ol> <p><b>机械与环境性能 Mechanical Data And Environmental Data:</b></p> <ol style="list-style-type: none"> <li>耐久性 Durability(matings): 500 times;</li> <li>温度范围 Temperature range: -55 to +125℃;</li> </ol> <p><b>材料及表面处理 Material Data:</b></p> <ol style="list-style-type: none"> <li>外导体 Outer Contact: 黄铜镀金 Brass gold-plated;</li> <li>内导体 Centre Contact: 锡青铜镀金 Tin bronze gold-plated;</li> <li>绝缘体 Insulator: PEI;</li> </ol>																																																																																								
<table border="1" style="width: 100%;"> <tr> <td colspan="2">SSMP-JR-2W40-02</td> <td>≤1.30 (DC-40GHz)</td> </tr> <tr> <td colspan="2">SSMP-JR-2W40-01</td> <td>≤1.20 (DC-40GHz)</td> </tr> <tr> <td colspan="2">P/N</td> <td>VSWR</td> </tr> </table>															SSMP-JR-2W40-02		≤1.30 (DC-40GHz)	SSMP-JR-2W40-01		≤1.20 (DC-40GHz)	P/N		VSWR																																																																	
SSMP-JR-2W40-02		≤1.30 (DC-40GHz)																																																																																						
SSMP-JR-2W40-01		≤1.20 (DC-40GHz)																																																																																						
P/N		VSWR																																																																																						
<table border="1" style="width: 100%;"> <tr> <td colspan="4">未注形位公差 GENERAL TOLERANCE OF FORM AND LOCATION</td> <td colspan="2">GB/T 1184-H</td> <td colspan="5" rowspan="2"> </td> </tr> <tr> <td colspan="4">未注尺寸公差 GENERAL DIMENSIONAL TOLERANCE</td> <td>设计 DESIGN</td> <td>Caogang 20210616</td> </tr> <tr> <td colspan="4"></td> <td>校对 CHECK</td> <td>Xuyan 20210616</td> <td>描述 DESCRIPTION</td> <td colspan="5">SSMP公头(全擒纵)负载 SSMP Male (Full Detent) Load</td> </tr> <tr> <td>X. ±0.1</td> <td>X° . ±1°</td> <td>审核 AUDIT</td> <td>Qzheng 20210616</td> <td>名称 NAME</td> <td colspan="2">射频同轴负载 RF Coaxial Load</td> <td>图号 DWG No.</td> <td colspan="3">-</td> </tr> <tr> <td>. X ±0.05</td> <td>. X° ±0.5°</td> <td>工艺 TECHNICS</td> <td>LiLi 20210616</td> <td>视图 VIEW</td> <td></td> <td>产品型号 P/N</td> <td colspan="4">SSMP-JR-2W40-XX</td> </tr> <tr> <td>. XX ±0.05</td> <td>. XX° ±0.2°</td> <td>标审 STANDARDIZE</td> <td>WHlei 20210616</td> <td>比例 SCALE</td> <td>6:1</td> <td>表面积SURFACE AREA (mm<sup>2</sup>)</td> <td>-</td> <td>版本 REV.</td> <td colspan="2">V1.0</td> </tr> <tr> <td>. XXX ±0.02</td> <td>. XXX° ±0.1°</td> <td>批准 APPROVE</td> <td>TFsheng 20210616</td> <td>单位 UNIT</td> <td>mm</td> <td>图幅 SIZE</td> <td>A4</td> <td>重量 WEIGHT (g)</td> <td>-</td> <td>页码 SHEET OF</td> <td>1/1</td> </tr> </table>															未注形位公差 GENERAL TOLERANCE OF FORM AND LOCATION				GB/T 1184-H							未注尺寸公差 GENERAL DIMENSIONAL TOLERANCE				设计 DESIGN	Caogang 20210616					校对 CHECK	Xuyan 20210616	描述 DESCRIPTION	SSMP公头(全擒纵)负载 SSMP Male (Full Detent) Load					X. ±0.1	X° . ±1°	审核 AUDIT	Qzheng 20210616	名称 NAME	射频同轴负载 RF Coaxial Load		图号 DWG No.	-			. X ±0.05	. X° ±0.5°	工艺 TECHNICS	LiLi 20210616	视图 VIEW		产品型号 P/N	SSMP-JR-2W40-XX				. XX ±0.05	. XX° ±0.2°	标审 STANDARDIZE	WHlei 20210616	比例 SCALE	6:1	表面积SURFACE AREA (mm <sup>2</sup> )	-	版本 REV.	V1.0		. XXX ±0.02	. XXX° ±0.1°	批准 APPROVE	TFsheng 20210616	单位 UNIT	mm	图幅 SIZE	A4	重量 WEIGHT (g)	-	页码 SHEET OF	1/1
未注形位公差 GENERAL TOLERANCE OF FORM AND LOCATION				GB/T 1184-H																																																																																				
未注尺寸公差 GENERAL DIMENSIONAL TOLERANCE				设计 DESIGN	Caogang 20210616																																																																																			
				校对 CHECK	Xuyan 20210616	描述 DESCRIPTION	SSMP公头(全擒纵)负载 SSMP Male (Full Detent) Load																																																																																	
X. ±0.1	X° . ±1°	审核 AUDIT	Qzheng 20210616	名称 NAME	射频同轴负载 RF Coaxial Load		图号 DWG No.	-																																																																																
. X ±0.05	. X° ±0.5°	工艺 TECHNICS	LiLi 20210616	视图 VIEW		产品型号 P/N	SSMP-JR-2W40-XX																																																																																	
. XX ±0.05	. XX° ±0.2°	标审 STANDARDIZE	WHlei 20210616	比例 SCALE	6:1	表面积SURFACE AREA (mm <sup>2</sup> )	-	版本 REV.	V1.0																																																																															
. XXX ±0.02	. XXX° ±0.1°	批准 APPROVE	TFsheng 20210616	单位 UNIT	mm	图幅 SIZE	A4	重量 WEIGHT (g)	-	页码 SHEET OF	1/1																																																																													
<table border="1" style="width: 100%;"> <tr> <td>关键尺寸 CRITICAL DIMENSION *</td> <td colspan="14"></td> </tr> </table>															关键尺寸 CRITICAL DIMENSION *																																																																									
关键尺寸 CRITICAL DIMENSION *																																																																																								
1	2		3		4		5		6		7		8																																																																											