

1	2		3	4	5		6		7		8																																																																											
					标记 SIGN	版本 REV.	描述 DESCRIPTION		变更人 ORIGINATOR	日期 DATE	更改单号 REVISE NO.																																																																											
					/	/	新版发行 NEW EDITION		/	/	/																																																																											
<p>执行标准 Standard according to:GJB360B,MIL-STD-202</p> <p>电气性能 Electrical Data:</p> <ol style="list-style-type: none"> 特性阻抗 Impedance:50 Ω; 频率范围 Frequency range:DC-40GHz; 电压驻波比 VSWR:≤见附表 See table; 平均功率 Mean power:2W; <p>机械与环境性能 Mechanical Data And Environmental Data:</p> <ol style="list-style-type: none"> 耐久性 Durability(matings):500 times; 温度范围 Temperature range:-55 to +125℃; <p>材料及表面处理 Material Data:</p> <ol style="list-style-type: none"> 外导体 Outer Contact:铍铜镀金 Beryllium copper gold-plated; 内导体 Centre Contact:铍铜镀金 Beryllium copper gold-plated; 绝缘体 Insulator:PTFE; 																																																																																						
<table border="1" style="width: 100%;"> <tr> <td>SSMP-KR-2W40-02</td> <td>≤1.30 (DC-40GHz)</td> </tr> <tr> <td>SSMP-KR-2W40-01</td> <td>≤1.20 (DC-40GHz)</td> </tr> <tr> <td>P/N</td> <td>VSWR</td> </tr> </table>													SSMP-KR-2W40-02	≤1.30 (DC-40GHz)	SSMP-KR-2W40-01	≤1.20 (DC-40GHz)	P/N	VSWR																																																																				
SSMP-KR-2W40-02	≤1.30 (DC-40GHz)																																																																																					
SSMP-KR-2W40-01	≤1.20 (DC-40GHz)																																																																																					
P/N	VSWR																																																																																					
<table border="1" style="width: 100%;"> <tr> <td colspan="2">未注形位公差 GENERAL TOLERANCE OF FORM AND LOCATION</td> <td colspan="2">GB/T 1184-H</td> <td colspan="6" rowspan="2" style="text-align: center;"> </td> </tr> <tr> <td colspan="2">未注尺寸公差 GENERAL DIMENSIONAL TOLERANCE</td> <td>设计 DESIGN</td> <td>Caogang 20210616</td> </tr> <tr> <td colspan="2"></td> <td>校对 CHECK</td> <td>Xuyan 20210616</td> <td>描述 DESCRIPTION</td> <td colspan="7">SSMP母头负载 SSMP Female Load</td> </tr> <tr> <td>X. ±0.1</td> <td>X° .±1°</td> <td>审核 AUDIT</td> <td>Qzheng 20210616</td> <td>名称 NAME</td> <td colspan="2">射频同轴负载 RF Coaxial Load</td> <td>图号 DWG No.</td> <td colspan="4">-</td> </tr> <tr> <td>.X±0.05</td> <td>.X° ±0.5°</td> <td>工艺 TECHNICS</td> <td>LiLi 20210616</td> <td>视图 VIEW</td> <td></td> <td colspan="2">产品型号 P/N</td> <td colspan="4">SSMP-KR-2W40-XX</td> </tr> <tr> <td>.XX±0.05</td> <td>.XX° ±0.2°</td> <td>标审 STANDARDIZE</td> <td>WHlei 20210616</td> <td>比例 SCALE</td> <td colspan="2">8:1</td> <td>表面积SURFACE AREA (mm²)</td> <td>-</td> <td>版本 REV.</td> <td colspan="2">V1.0</td> </tr> <tr> <td>.XXX±0.02</td> <td>.XXX° ±0.1°</td> <td>批准 APPROVE</td> <td>TFsheng 20210616</td> <td>单位 UNIT</td> <td>mm</td> <td>图幅 SIZE</td> <td>A4</td> <td>重量 WEIGHT (g)</td> <td>-</td> <td>页码 SHEET OF</td> <td colspan="1">1/1</td> </tr> </table>													未注形位公差 GENERAL TOLERANCE OF FORM AND LOCATION		GB/T 1184-H								未注尺寸公差 GENERAL DIMENSIONAL TOLERANCE		设计 DESIGN	Caogang 20210616			校对 CHECK	Xuyan 20210616	描述 DESCRIPTION	SSMP母头负载 SSMP Female Load							X. ±0.1	X° .±1°	审核 AUDIT	Qzheng 20210616	名称 NAME	射频同轴负载 RF Coaxial Load		图号 DWG No.	-				.X±0.05	.X° ±0.5°	工艺 TECHNICS	LiLi 20210616	视图 VIEW		产品型号 P/N		SSMP-KR-2W40-XX				.XX±0.05	.XX° ±0.2°	标审 STANDARDIZE	WHlei 20210616	比例 SCALE	8:1		表面积SURFACE AREA (mm ²)	-	版本 REV.	V1.0		.XXX±0.02	.XXX° ±0.1°	批准 APPROVE	TFsheng 20210616	单位 UNIT	mm	图幅 SIZE	A4	重量 WEIGHT (g)	-	页码 SHEET OF	1/1
未注形位公差 GENERAL TOLERANCE OF FORM AND LOCATION		GB/T 1184-H																																																																																				
未注尺寸公差 GENERAL DIMENSIONAL TOLERANCE		设计 DESIGN	Caogang 20210616																																																																																			
		校对 CHECK	Xuyan 20210616	描述 DESCRIPTION	SSMP母头负载 SSMP Female Load																																																																																	
X. ±0.1	X° .±1°	审核 AUDIT	Qzheng 20210616	名称 NAME	射频同轴负载 RF Coaxial Load		图号 DWG No.	-																																																																														
.X±0.05	.X° ±0.5°	工艺 TECHNICS	LiLi 20210616	视图 VIEW		产品型号 P/N		SSMP-KR-2W40-XX																																																																														
.XX±0.05	.XX° ±0.2°	标审 STANDARDIZE	WHlei 20210616	比例 SCALE	8:1		表面积SURFACE AREA (mm ²)	-	版本 REV.	V1.0																																																																												
.XXX±0.02	.XXX° ±0.1°	批准 APPROVE	TFsheng 20210616	单位 UNIT	mm	图幅 SIZE	A4	重量 WEIGHT (g)	-	页码 SHEET OF	1/1																																																																											
<table border="1" style="width: 100%;"> <tr> <td>关键尺寸 CRITICAL DIMENSION *</td> <td colspan="12"></td> </tr> <tr> <td>1</td> <td colspan="2">2</td> <td colspan="1">3</td> <td colspan="1">4</td> <td colspan="2">5</td> <td colspan="2">6</td> <td colspan="2">7</td> <td colspan="2">8</td> </tr> </table>													关键尺寸 CRITICAL DIMENSION *													1	2		3	4	5		6		7		8																																																	
关键尺寸 CRITICAL DIMENSION *																																																																																						
1	2		3	4	5		6		7		8																																																																											