

**型号 Cable Type : LA360**

LA系列超低损耗稳幅稳相电缆

Ultra-low Loss Amplitude and Phase Stable Cable



结构 Construction	材料 Materials	尺寸 O.D (mm)
1.中心导体 Center Conductor	镀银铜 Silvered Copper	0.91
2.绝缘层 Dielectric	低密度聚四氟乙烯 Low Density PTFE	2.50
3.内屏蔽层 Inner Shield	镀银铜带绕包 Silvered Copper Tape Wrapping	2.66
4.外屏蔽层 Outer Shield	镀银铜丝编织 Braided Silvered Copper Wire	3.11
5.护套 Jacket	灰色氟塑料 Grey PFA	3.60

电气性能 Electrical Specifications	
阻抗 Cable Impedance	50 Ω
速率 Velocity	82%
屏蔽效率 Shielding Effectiveness	>90 dB
耐电压 Voltage Withstanding	500 V DC
工作频率 Operating Frequency	DC-40 GHz
弯曲幅度稳定性 Amplitude Stability vs Flexure	<±0.1 dB
机械相位稳定性 Mechanical Phase Stability	<±5°

机械环境性能 Mechanical & Environmental Specifications	
重量 Weight	33 g/m
弯曲半径, 静态 Bend Radius, static	18 mm
弯曲半径, 动态 Bend Radius, dynamic	36 mm
温度范围 Temperature Range	-55 ~ +165 °C

衰减典型值 Attenuation (Typical Value @ 25°C & Sea Level)		
频率 Frequency (MHz)	功率 Power (W)	衰减 Attenuation (dB/m)
300	936	0.20
1000	509	0.38
3000	291	0.66
6000	203	0.94
8500	170	1.12
12400	139	1.37
18000	115	1.67
26500	93	2.05
40000	75	2.56